#### §461.20

(6) Subpart A—Cadmium Powder Production—PSNS.

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average.
	Metric units—mg/kg of cadmium powder produced English units—pounds per 1,000,000 pounds of cadmium powder pro- duced	
Cadmium Nickel Zinc Cobalt	1.31 3.61 6.70 0.92	0.53 2.43 2.76 0.46

### (7) Subpart A—Silver Powder Production—PSNS.

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average.
	Metric units—mg/kg of silver powder produced English units—pounds per 1,000,000 pounds of sil- ver powder produced	
Cadmium Nickel Silver Zinc Cobalt	0.64 1.77 0.93 3.27 0.45	0.26 1.19 0.39 1.35 0.22

### (8) Subpart A—Cadmium Hydroxide Production—PSNS.

Maximum for any 1 day	Maximum for monthly average
Metric units—mg/kg of cadmium used	
English units—pounds per 1,000,000 pounds of cadmium used	
0.028	0.011
0.077	0.051
0.142	0.058
0.019	0.009
	for any 1 day  Metric units cadmiu English units 1,000,000 cadmium us  0.028 0.077 0.142

# (9) Subpart A—Nickel Hydroxide Production—PSNS.

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of nickel used	
	English units—pounds per 1,000,000 pounds of nickel used	
Cadmium	3.30	1.32
Nickel	9.08	6.11
Zinc	16.83	6.93
Cobalt	2.31	1.16

(b) There shall be no discharge allowance for process wastewater pollutants from any battery manufacturing operation other than those battery manufacturing operations listed above.

### Subpart B—Calcium Subcategory

# § 461.20 Applicability; description of the calcium subcategory.

This subpart applies to discharges to waters of the United States and introductions of pollutants into publicly owned treatment works from manufacturing calcium anode batteries.

#### §§ 461.21-461.22 [Reserved]

### § 461.23 New source performance standards (NSPS).

- (a) The discharge of wastewater pollutants from any new source subject to this subpart shall not exceed the standards set forth below.
- (b) There shall be no discharge for process wastewater pollutants from any battery manufacturing operations.

#### § 461.24 [Reserved]

### § 461.25 Pretreatment standards for new sources (PSNS).

- (a) Except as provided in §403.7 any new source subject to this subpart that introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the pretreatment standards for new sources listed below.
- (b) There shall be no discharge for process wastewater pollutants from any battery manufacturing operations.

### Subpart C—Lead Subcategory

### § 461.30 Applicability; description of the lead subcategory.

This subpart applies to discharges to waters of the United States and introduction of pollutants into publicly owned treatment works from the manufacturing of lead anode batteries.